

## Key Features

- High Ripple Current: up to 4A
- Ammo pack taping (Φ8 and Φ10 products)
- Low ESR
- Rated voltage: 25V 80V
- Endurance: 10.000h @105°C to 1.000h@150°C\*
- Temperature range: -55°C to 150°C\*
- AEC-Q200 compliant
- \*depending on series

## Conductive Polymer Hybrid Aluminum Electrolytic Capacitors - THT Type


## Panasonic INDUSTRY

## Hybrid Capacitor all series as THT

In many industries, THT type capacitors are still needed. Panasonic answers this demand by offering THT types of all Hybrid Capacitor series. They achieve low ESR (down to  $11 \text{m}\Omega$ ), withstand high voltage and offer high reliability through the use of "hybrid electrolyte" - consisting of conductive polymer and electrolytic liquid. With the same specifications as SMD type, THT type covers a Capacitance of up to  $560 \mu\text{F}$ , supporting 25 V - 80 V with an endurance from  $10.000 \text{h}@105^{\circ}\text{C}$  to  $1.000 \text{h}@150^{\circ}\text{C}$ . All series for Polymer Hybrid capacitor can support THT ammo pack taping ( $\Phi$ 8 and  $\Phi$ 10 products are available).









For further information, please contact <a href="mailto:capacitor@eu.panasonic.com">capacitor@eu.panasonic.com</a>