Panasonic ideas for life

Programmable Display

GT12

Bright and Vivid



4.6-inch screen
Industry's top in brightness in its class
The first SD memory card slot in its class
Equipped with a mini USB port and IP67-rated body



GT12

Programmable Display

The 4.6-inch wide screen provides highest visual quality


	4.6-inch monochrome	32 characters x 12 lines	Free layout	Through function	
I	3-color backlight	320 x 120 dots	RS232C/RS422 (RS485)	24VDC	

Top-class viewability *1

- 4.6-inch screen
- · LED backlight with high brightness
- Crisp images produced by the high-definition Half-QVGA (320 x 120) LCD
- Analog touch system with no annoying visible dots or lines on the display



Cool and sophisticated body full of useful features




Flexible sizing and layout available for switches and characters

- Switches with a minimum size of 8 x 8 dots can be moved in increments of 1 dot
- A wide range of character fonts and sizes (10 to 120 dots) are supported
- Multi-function switches are supported



Multi-connection of up to 32 units is possible *2



Product types

Product name	Description				Part number			
GT12 main unit	STN monochrome (green/orange/red backlight)	- 24V	RS232C	Pure black	AIG12GQ12D			
				Hairline silver	AIG12GQ13D			
			RS422 (RS485)	Pure black	AIG12GQ14D			
				Hairline silver	AIG12GQ15D			
	STN monochrome (white/pink/red backlight)		RS232C	Pure black	AIG12MQ12D			
				Hairline silver	AIG12MQ13D			
			RS422 (RS485)	Pure black	AIG12MQ14D			
				Hairline silver	AIG12MQ15D			
Terminal GTWIN Ver.2 English version tool kit	Terminal GTWIN CD-ROM, GT Series Technical Manual (English version)				AIGT8001V2			
PLC connection cable	Cable for connecting GT12 and our PLC, 5-pin mini-DIN connector — single wires				AIGT8192D			
Panel face protection sheets	For GT12, 10 sheets in a set				AIGT12800			
GT12 programming cable	USB-Programming cable, USB A to USB-B mini, 2m				CABMINIUSB5D			

^{*1:} Based on our research as of May 27, 2009

^{*2:} With our FP series PLC