

Explanation of part numbers

◇ Part number system

• Surface mount type

16 Rated voltage	SVP Series	3R3 Rated capacitance	M Capacitance tolerance																																																												
↓	↓	↓	↓																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">R.voltage (V)</th> <th style="width: 50%;">Code</th> </tr> </thead> <tbody> <tr><td>2.0</td><td>2</td></tr> <tr><td>2.5</td><td>2R5</td></tr> <tr><td>4.0</td><td>4</td></tr> <tr><td>6.3</td><td>6</td></tr> <tr><td>10</td><td>10</td></tr> <tr><td>16</td><td>16</td></tr> <tr><td>20</td><td>20</td></tr> <tr><td>25</td><td>25</td></tr> <tr><td>35</td><td>35</td></tr> <tr><td>100</td><td>100</td></tr> </tbody> </table>	R.voltage (V)	Code	2.0	2	2.5	2R5	4.0	4	6.3	6	10	10	16	16	20	20	25	25	35	35	100	100	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 100%;">Series</th> </tr> </thead> <tbody> <tr><td>SVT</td></tr> <tr><td>SVPT</td></tr> <tr><td>SVF</td></tr> <tr><td>SVPK</td></tr> <tr><td>SXV</td></tr> <tr><td>SVPG</td></tr> <tr><td>SVPF</td></tr> <tr><td>SVPA</td></tr> <tr><td>SVPB</td></tr> <tr><td>SVPC</td></tr> <tr><td>SVPD</td></tr> <tr><td>SVPE</td></tr> <tr><td>SVPS</td></tr> <tr><td>SVQP</td></tr> <tr><td>SVP</td></tr> </tbody> </table>	Series	SVT	SVPT	SVF	SVPK	SXV	SVPG	SVPF	SVPA	SVPB	SVPC	SVPD	SVPE	SVPS	SVQP	SVP	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">R.capacitance (μF)</th> <th style="width: 50%;">Code</th> </tr> </thead> <tbody> <tr><td>3.3</td><td>3R3</td></tr> <tr><td>4.7</td><td>4R7</td></tr> <tr><td>10</td><td>10</td></tr> <tr><td>22</td><td>22</td></tr> <tr><td>100</td><td>100</td></tr> <tr><td>220</td><td>220</td></tr> <tr><td>470</td><td>470</td></tr> <tr><td>1500</td><td>1500</td></tr> </tbody> </table>	R.capacitance (μF)	Code	3.3	3R3	4.7	4R7	10	10	22	22	100	100	220	220	470	470	1500	1500	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Cap. tolerance</th> <th style="width: 50%;">Code</th> </tr> </thead> <tbody> <tr><td>±20%</td><td>M</td></tr> </tbody> </table>	Cap. tolerance	Code	±20%	M
R.voltage (V)	Code																																																														
2.0	2																																																														
2.5	2R5																																																														
4.0	4																																																														
6.3	6																																																														
10	10																																																														
16	16																																																														
20	20																																																														
25	25																																																														
35	35																																																														
100	100																																																														
Series																																																															
SVT																																																															
SVPT																																																															
SVF																																																															
SVPK																																																															
SXV																																																															
SVPG																																																															
SVPF																																																															
SVPA																																																															
SVPB																																																															
SVPC																																																															
SVPD																																																															
SVPE																																																															
SVPS																																																															
SVQP																																																															
SVP																																																															
R.capacitance (μF)	Code																																																														
3.3	3R3																																																														
4.7	4R7																																																														
10	10																																																														
22	22																																																														
100	100																																																														
220	220																																																														
470	470																																																														
1500	1500																																																														
Cap. tolerance	Code																																																														
±20%	M																																																														

• Radial lead type

16 Rated voltage	SEPC Series	470 Rated capacitance	M Capacitance tolerance	T Taping or forming of terminal code																																																			
↓	↓	↓	↓	↓																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">R.voltage (V)</th> <th style="width: 50%;">Code</th> </tr> </thead> <tbody> <tr><td>2.5</td><td>2R5^{※1}</td></tr> <tr><td>4.0</td><td>4</td></tr> <tr><td>6.3</td><td>6</td></tr> <tr><td>10</td><td>10</td></tr> <tr><td>16</td><td>16</td></tr> <tr><td>20</td><td>20</td></tr> <tr><td>25</td><td>25</td></tr> <tr><td>32</td><td>32</td></tr> <tr><td>100</td><td>100</td></tr> </tbody> </table>	R.voltage (V)	Code	2.5	2R5 ^{※1}	4.0	4	6.3	6	10	10	16	16	20	20	25	25	32	32	100	100	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 100%;">Series</th> </tr> </thead> <tbody> <tr><td>SEF</td></tr> <tr><td>SEK</td></tr> <tr><td>SEPG</td></tr> <tr><td>SXE</td></tr> <tr><td>SEPC</td></tr> <tr><td>SEPF</td></tr> <tr><td>SEQP</td></tr> <tr><td>SEP</td></tr> </tbody> </table>	Series	SEF	SEK	SEPG	SXE	SEPC	SEPF	SEQP	SEP	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">R.capacitance (μF)</th> <th style="width: 50%;">Code</th> </tr> </thead> <tbody> <tr><td>6.8</td><td>6R8</td></tr> <tr><td>10</td><td>10</td></tr> <tr><td>22</td><td>22</td></tr> <tr><td>100</td><td>100</td></tr> <tr><td>220</td><td>220</td></tr> <tr><td>470</td><td>470</td></tr> <tr><td>1000</td><td>1000</td></tr> <tr><td>2700</td><td>2700</td></tr> </tbody> </table>	R.capacitance (μF)	Code	6.8	6R8	10	10	22	22	100	100	220	220	470	470	1000	1000	2700	2700	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Cap. tolerance</th> <th style="width: 50%;">Code</th> </tr> </thead> <tbody> <tr><td>±20%</td><td>M</td></tr> </tbody> </table>	Cap. tolerance	Code	±20%	M	<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: auto;"> <p>Taping of lead terminal wire process code. None suffix for regular length lead type products.</p> </div>
R.voltage (V)	Code																																																						
2.5	2R5 ^{※1}																																																						
4.0	4																																																						
6.3	6																																																						
10	10																																																						
16	16																																																						
20	20																																																						
25	25																																																						
32	32																																																						
100	100																																																						
Series																																																							
SEF																																																							
SEK																																																							
SEPG																																																							
SXE																																																							
SEPC																																																							
SEPF																																																							
SEQP																																																							
SEP																																																							
R.capacitance (μF)	Code																																																						
6.8	6R8																																																						
10	10																																																						
22	22																																																						
100	100																																																						
220	220																																																						
470	470																																																						
1000	1000																																																						
2700	2700																																																						
Cap. tolerance	Code																																																						
±20%	M																																																						

※1 Code 2 is used for 2.5 V products of B9, C6, C9, E7, E9 and F13 size in SEPC series.